

Category: Air Conditioner

written by www.mbsmpro.com | February 9, 2026



The Unionaire PUQ012HR5R0WPK is a robust 12,000 BTU reversible heat pump system designed for demanding climates. Utilizing an R22 rotary compressor, this unit balances efficiency and reliability. Our technical breakdown covers electrical parameters, pressure ratings, and compatible replacements, providing field workers with the essential data needed for professional maintenance, system repairs, and component sourcing.

---

## **Unionaire PUJ012HR5R0WPK 12000 BTU Heat Pump R22 Technical Specifications and Compressor Replacement Guide**

Category: Air Conditioner,Mbsmpro

written by www.mbsmpro.com | February 9, 2026



## **Mbsm.pro, Unionaire, PUJ012HR5R0WPK, 12000 BTU, 1.5 HP, Heat Pump, R22, 220V, Cooling and Heating**

When working in the HVAC field, encountering a Unionaire system is quite common, especially in regions requiring robust performance under high ambient temperatures. The PUJ012HR5R0WPK is a classic example of a reliable reversible heat pump designed to handle both the scorching summer heat and the chill of winter. As a technician, seeing these specifications tells a clear story of a 1-ton (12,000 BTU) system built for durability and efficiency.

The heart of this system is its rotary compressor, optimized for R22 refrigerant. While R22 is being

phased out globally, many of these units remain in service because of their heavy-duty build quality. With a cooling and heating capacity of 3.52 kW, this model provides a balanced thermal load for standard residential or small commercial spaces.

## Technical Performance and Engineering Insight

From an engineering perspective, the electrical characteristics of this unit are standard but precise. With a Rated Load Amperage (RLA) of 6A for the compressor and a Locked Rotor Amperage (LRA) of 31A, the electrical draw is manageable for most residential circuits, provided a 10A fuse or circuit breaker is utilized.

The design pressures are particularly noteworthy. A high-side pressure of 400 PSI and a low-side of 82 PSI indicate a system that operates comfortably within the safety margins of R22, ensuring longevity even when the outdoor unit is exposed to intense sun. The 0.850 kg refrigerant charge is a relatively small amount for a 12,000 BTU unit, reflecting an efficient heat exchanger design that maximizes every gram of gas.

## Efficiency Metrics (COP)

Efficiency in a heat pump is measured by the Coefficient of Performance. Below is a breakdown of estimated performance across various evaporating temperatures for a compressor of this class.

Evaporating Temp (°C)	Cooling Capacity (Watts)	Power Consumption (Watts)	COP (W/W)
10	4100	1150	3.56
7.2 (Standard Rating)	3520	1080	3.26
5	3200	1020	3.13
0	2650	950	2.78
-5	2150	880	2.44
-10	1700	820	2.07

## Technical Specification Table: Unionaire PUJ012HR5R0WPK

Data Point	Specification
<b>Model</b>	PUJ012HR5R0WPK
<b>Utilisation</b>	HBP (High Back Pressure)
<b>Domaine</b>	Comfort Cooling & Heating (Heat Pump)
<b>Cooling Wattage at -23°C</b>	N/A (AC Application)
<b>Cubic feet/Litres capacity</b>	Effectively cools rooms approx. 150-250 sq. ft.
<b>Kcal/h</b>	3024 Kcal/h
<b>Oil Type and Quantity</b>	Mineral Oil (SUNISO 3GS or equivalent), ~350ml
<b>Horsepower (HP)</b>	1.5 HP
<b>Refrigerant Type</b>	R22
<b>Power Supply</b>	220-240V / 50Hz / 1 Phase
<b>Cooling Capacity BTU</b>	12,000 BTU/h
<b>Motor Type</b>	Permanent Split Capacitor (PSC)
<b>Displacement</b>	Approx. 16.0 to 18.0 cc
<b>Winding Material</b>	Copper

<b>Pression Charge</b>	High: 400 PSI / Low: 82 PSI
<b>Capillary Size</b>	0.054" x 30" (Typical for 12k BTU AC)
<b>Recommended Application</b>	Split Unit Air Conditioners
<b>Temperature Function</b>	Reversible (Cooling/Heating)
<b>Fan Requirement</b>	Yes (Forced Air Condenser)
<b>Commercial Use</b>	Yes (Light Commercial/Residential)
<b>Amperage in Function (RLA)</b>	6.0 A
<b>Locked Rotor Amps (LRA)</b>	31.0 A
<b>Type of Relay</b>	Potential Relay or Start Kit (Optional)
<b>Capacitor Value</b>	30uF or 35uF / 450V
<b>Country of Origin</b>	Made in Egypt

## Compressor Replacement Guide

If the original compressor in the PUJ012HR5R0WPK fails, finding an exact match or a compatible alternative is essential for maintaining system balance.

### 5 Direct Replacements (R22 Gas)

1. **GMCC** - PH215X2C-4FT1 (Highly reliable rotary)
2. **Highly (Hitachi)** - ASD102SK
3. **LG** - QJ222P
4. **Panasonic** - 2K22C225A
5. **Samsung** - UR4D124

### 5 Replacements (Alternative Refrigerant / Conversion)

*Note: Converting from R22 to other gases often requires oil changes and capillary adjustments.*

1. **GMCC (R410A)** - PA145X2C-4FZ1 (Requires system modification)
2. **Tecumseh (R404A)** - AE4440Z (For MBP applications)
3. **Danfoss (R407C)** - HRP034T4
4. **Copeland (R134a)** - ARE37C3E (Only for specific low-pressure setups)
5. **Bristol (R22/R407C)** - H23A153DBEA

## Technician's Advice and Maintenance Notice

1. **Refrigerant Charge:** Always use a scale. The nameplate specifies exactly 0.850 kg. Overcharging this unit will lead to high head pressure and premature compressor failure, especially in a heat pump where the reversing valve adds complexity.
2. **Electrical Protection:** Ensure the 10A breaker is dedicated. If the LRA (31A) is hit frequently due to short-cycling, the windings will degrade. Installing a "Hard Start Kit" can significantly

extend the life of older compressors in this model.

3. **Reversing Valve Check:** Since this is a heat pump, if you find the unit is not cooling but the compressor is running, check the solenoid on the reversing valve before assuming the compressor is faulty.
4. **Clean Coils:** A 12,000 BTU unit relies heavily on airflow. Clogged condenser fins will quickly push the high-side pressure above the 400 PSI design limit.

**Focus Keyphrase:** Unionaire PUJ012HR5R0WPK 12000 BTU Heat Pump R22 Technical Specifications and Compressor Replacement Guide

**SEO Title:** Mbsm.pro, Unionaire, PUJ012HR5R0WPK, 12000 BTU, 1.5 HP, Heat Pump, R22, 220V, Cooling and Heating

**Meta Description:** Discover the full specs for the Unionaire PUJ012HR5R0WPK heat pump. Includes R22 charge data, electrical RLA/LRA ratings, and a comprehensive compressor replacement guide for technicians.

**Slug:** unionaire-puj012hr5r0wpk-12000-btu-heat-pump-specs

**Tags:** Unionaire, PUJ012HR5R0WPK, 12000 BTU, 1.5 HP, R22, Heat Pump, Compressor Replacement, GMCC PH215X2C, Highly ASD102SK, LG QJ222P, Panasonic 2K22C, Samsung UR4D124, Mbsmgroup, Mbsm.pro, mbsmpro.com, mbsm

**Excerpt:** The Unionaire PUJ012HR5R0WPK is a robust 12,000 BTU (1.5 HP) heat pump system designed for efficient cooling and heating. Utilizing R22 refrigerant with an 850g charge, this 220V/50Hz unit is a staple in residential HVAC. Our guide covers its electrical RLA/LRA specs, design pressures, and provides a detailed list of compatible compressor replacements.



Unionaire PUJ012HR5R0WPK 12000 BTU Heat Pump R22 Technical Specifications and Compressor Replacement Guide mbsmpro

[mbsmpro.com](http://mbsmpro.com)-Unionaire PUJ012HR5R0WPK 12000 BTU Heat Pump R22 Technical Specifications and Compressor ReplacementDownload

## Unionaire G+ ITWG 022 R5 Air Conditioner Specifications, 21500 BTU Cooling Capacity, Technical Manual and Installation Guide

Category: Air Conditioner,Mbsmpro  
written by www.mbsmpro.com | February 9, 2026



The Unionaire G+ ITWG 022 R5 represents a robust cooling solution engineered for demanding Mediterranean and Middle Eastern climates. Delivering a potent 21,500 BTU/Hr cooling capacity, this Egyptian-manufactured indoor unit balances high-volume airflow with structural durability. Designed for 220-240V/50Hz systems, it features an IPX4 rating and a compact 12.5 kg chassis for versatile wall-mounted installation.