

1N4728, 1N4729, 1N4730, 1N4731, 1N4732, 1N4733, 1N4734, 1N4735, 1N4736, 1N4737, Zener diode

Category: Electronic

written by www.mbsmpro.com | January 5, 2026




Zener diodes like the 1N4728A thru 1N4737A series deliver reliable voltage regulation from 3.3V to 7.5V at 1W power. Engineers rely on these for stabilizing circuits in power supplies and protection setups. Check the full voltage chart and specs below for your next project. (55 words)

8-pin and 11-pin relay bases are common in control panels

Category: Global Electric

written by www.mbsmpro.com | January 5, 2026



8-pin and 11-pin relay bases are common in control panels, but miswiring coil and contact terminals can burn a load or keep a circuit from switching. This guide explains each pin function, shows practical wiring logic for NO/NC contacts, and compares 8-pin DPDT sockets with 11-pin 3PDT sockets for automation work in HVAC retrofits today.

Gas Charging or Vacuuming

Category: Refrigeration

written by www.mbsmpro.com | January 5, 2026



The copper tube assembly shown is a service charging valve on the liquid line of a small hermetic refrigeration unit. This single access point can be used for deep vacuum and for refrigerant charging, depending on the connected equipment. Understanding when the technician is vacuuming and when charging is critical for reliability.

BASIC TN1900 Refrigerator Compressor

Category: Refrigeration

written by www.mbsmpro.com | January 5, 2026



The BASIC TN1900 represents a medium-displacement hermetic reciprocating compressor engineered for low back pressure refrigeration applications. This Syrian-manufactured unit operates on R134a refrigerant with 220-240V 50/60Hz power supply, delivering 200-250W cooling capacity at -30°C to -10°C evaporating temperatures with RSIR motor technology

HITACHI FL20S88NAA Compressor

Category: Refrigeration

written by www.mbsmpro.com | January 5, 2026



The HITACHI FL20S88NAA 0.75 HP hermetic scroll compressor delivers 256W cooling capacity at 50Hz, utilizing HFC-134a refrigerant for household refrigerator-freezer applications. This LBP-classified unit operates reliably at 220-240V with RSIR starting method, integrated into Sharp's SJ-PT73R-HS3 model offering 662-liter gross capacity with Hybrid Cooling System and Plasmacluster technology.

Transformer, WDB4109, 220V 50Hz, Microwave Standby Power

Category: Electronic

written by www.mbsmpro.com | January 5, 2026



The WDB4109 is a compact linear transformer used as the standby power source in many Samsung microwave ovens, converting 220 V - 230 V AC to 16.33 V and dual 5.47 V outputs for the control board. It is critical for powering the clock, keypad, relays and low-voltage electronics safely.

Relay, model MAA-S-124-C, is a 24 VDC, 5-pin

Category: Mbsmpro

written by www.mbsmpro.com | January 5, 2026




The MEISHUO S220 series relay, model MAA-S-124-C, is a 24-volt 5-pin SPDT automotive relay rated 20 A/10 A at 28 VDC. Its DIN 72552 terminal numbering—30, 85, 86, 87 and 87a—gives technicians a universal language for wiring and troubleshooting in vehicles, HVAC equipment and industrial control panels.

Types of Electrical Wires and Their Uses

Category: Mbsmpro

written by www.mbsmpro.com | January 5, 2026



Modern installations use several wire families, each optimized for voltage level, environment, flexibility, and temperature range. Choosing the right type reduces losses, prevents overheating, and keeps residential, industrial, and communication systems compliant with safety standards. PVC house wiring, flexible multi-core cables, armoured feeders, PTFE high-temperature conductors, and data or earth wires all play specific roles.

Embraco EM2Z 80HL.C compressor requires approximately 150 ml Oil

Category: Refrigeration

written by www.mbsmpro.com | January 5, 2026

