

Emkarate RL 68H Compatibility

Chart with HFC HCFC HFO

Site: Mbsmpro

Date: January 16, 2026 | **Author:** www.mbsmpro.com

URL: <https://mbsmpro.com/rl-68h-poe-oil-with-r600-refrigerant/>



Focus Keyphrase: Emkarate RL 68H Compatibility Chart with HFC HCFC HFO and Hydrocarbon Refrigerants

SEO Title: Mbsmpro.com, Emkarate RL 68H, Refrigeration Lubricant, POE Oil, Refrigerant Compatibility, R134a, R404A, R600a, R22, Ammonia Warning

Meta Description: Technical analysis of Emkarate RL 68H POE lubricant compatibility. Detailed guide on using synthetic oil with HFC, HCFC, HFO, and Hydrocarbon refrigerants like R600a.

Slug: emkarate-rl-68h-refrigerant-compatibility-technical-guide

Tags: Emkarate RL 68H, POE Lubricant, Refrigerant Compatibility, R134a, R600a, R22, Ammonia Compatibility, Mbsmgroup, Mbsm.pro, mbsmpro.com, mbsm, Synthetic Oil, Compressor Maintenance

Excerpt: Emkarate RL 68H is a high-performance synthetic polyol ester (POE) lubricant designed for modern refrigeration systems. Understanding its chemical compatibility across different refrigerant generations—from HFCs like R134a to hydrocarbons like R600a—is vital for system longevity. This guide breaks down compatibility, technical reasons for usage, and critical warnings for technicians.

**Mbsmpro.com, Emkarate RL 68H,
Refrigeration Lubricant, Synthetic
POE, ISO VG 68, Global Refrigerant**

Compatibility Guide

In the evolving landscape of HVAC-R technology, the choice of lubricant can determine the success or failure of a compressor. **Emkarate RL 68H** is a premium **Synthetic Polyol Ester (POE)** lubricant engineered to meet the demands of various cooling systems. As an engineer or field technician, understanding the chemical relationship between this oil and different gas categories is essential for maintaining high efficiency and preventing mechanical breakdown.

Comprehensive Compatibility Analysis: Emkarate RL 68H vs. Refrigerant Categories

The following table outlines how **RL 68H** interacts with major refrigerant classes, providing the technical reasoning behind each classification based on chemical behavior and miscibility.

Refrigerant Class	Common Examples	Compatibility Status	Technical Reasoning (The "Why")
HFC (Modern Generation)	R134a, R404A, R410A, R407C, R507	Fully Compatible	These gases are polar and specifically require POE oils for proper miscibility, ensuring oil returns to the compressor.

HCFC (Legacy Transition)	R22, R123, R401A, R402A	Compatible	Ideal for “Retrofit” operations when converting older systems from Mineral Oil to more environmentally friendly HFC blends.
HFO (Eco-Friendly Gen)	R1234yf, R1234ze	Compatible	Exhibits high chemical stability, making it suitable for new low Global Warming Potential (GWP) refrigerants.
HC (Hydrocarbons)	R600a, R290	Chemically Compatible	Miscibility is excellent, but viscosity is the barrier; small HC systems typically require lower viscosity (ISO 10-32).

**Natural
(Carbon
Dioxide)**

R744

Compatible

RL 68H is robust enough to handle the high pressures and discharge temperatures typical of CO2 systems.

NEVER use with Ammonia. POE oils react chemically with R717, leading to sludge, corrosion, and system failure.

Ammonia

R717

**NOT
Compatible**

Deep Dive: The Relationship with R600a and Hydrocarbons

While **Emkarate RL 68H** is chemically “safe” for R600a (meaning it won’t break down the oil structure), there is a significant engineering caveat regarding **Viscosity**.

Most domestic R600a compressors are designed for low-viscosity oils (often Mineral or Alkylbenzene). Using an **ISO VG 68** oil in a system designed for **ISO 15 or 22** creates internal drag. This increased resistance puts unnecessary load on the motor, leading to higher energy consumption and potential starting issues in cold environments. Therefore, while it is compatible in a laboratory sense, it is often too “heavy” for standard

domestic refrigerators.

Engineering Value and Performance Comparison

When comparing **Emkarate RL 68H** to standard Mineral Oils (MO) or lower-grade synthetics, the performance benefits are clear in high-load scenarios.

Stability and Protection Factors:

- **Oxidation Resistance:** Synthetic POE resists breakdown much better than mineral oils when exposed to heat.
- **Wear Protection:** The film strength of ISO 68 is superior for commercial-grade compressors (e.g., 2 HP to 10 HP units), providing a thick protective layer on bearings.
- **Miscibility Range:** It maintains flow and return characteristics across a wider temperature spectrum than traditional lubricants.

Lubricant	Emkarate RL 68H	Standard Mineral
Property	(POE)	Oil (MO)
Base Fluid	Synthetic Ester	Petroleum Based
Moisture Sensitivity	High (Hygroscopic)	Low
Thermal Range	Excellent (High/Low)	Moderate
Application	HFC / Retrofit	CFC / HCFC / Ammonia

Expert Notices and Professional Advice

1. The Ammonia Rule:

As highlighted in our compatibility chart, **never introduce POE oil into an Ammonia (R717) system.** Ammonia requires Mineral Oils (MO) or Polyalphaolefins (PAO). The chemical reaction between POE and Ammonia creates soaps and acids that will destroy the compressor valves and seals.

2. Moisture is the Enemy:

POE oil is “thirsty.” It will pull moisture directly from the air. Always keep the cap tightly sealed. If a bottle has been open for more than a few minutes in a humid environment, its dielectric strength and chemical purity are compromised.

3. Retrofitting Legacy Systems:

When converting an R22 system to an HFC blend (like R422D), RL 68H is the industry standard for flushing. It helps carry residual mineral oil back to the separator, ensuring a clean transition.

Technical Specifications Summary

- **Model:** Emkarate RL 68H
 - **Viscosity Grade:** ISO VG 68
 - **Application:** Commercial Refrigeration, Industrial Chillers, Retrofitting.
 - **Approvals:** Approved by major OEMs including Copeland, Bitzer, and Danfoss.
-

Final Engineering Verdict

The **Emkarate RL 68H** is a versatile powerhouse for modern HFC and HFO systems. While it offers a bridge for HCFC retrofits and possesses the chemical stability for CO2 and Hydrocarbons, the field technician must always respect the **viscosity requirements** of the specific compressor model and the strict **exclusion of Ammonia** environments. Correct lubrication is not just about the gas; it's about the mechanical harmony of the entire system.

14.5sinfoGoogle AI models may make mistakes, so double-che



RL 68H POE Oil with R600 Refrigerant mbsmpro

Latest Articles

- [Guide de Dépannage de la Carte Inverter : Climatiseur Kolin KSM-IW20WAE](#)
- [RCFF-2HP Capillary Tube for a Samsung 18000 BTU air conditioner](#)
- [Carbon brushes washing machine motors](#)
- [Chauffe-eau Junkers : Restauration d'un Classique](#)
- [WS57H Compressor, 1/6 hp, Capacitor Requirement 4mf](#)
- [Hisense inverter expert, installtion](#)
- [Copeland D3DS5-100X 10 HP Freezer Compressor](#)
- [Bitzer 6G-30.2Y: The High-Performance 30 HP Semi-Hermetic](#)
- [Réparer un chauffe-eau à gaz Olympic 6L](#)
- [Best piping practices for semi-hermetic systems](#)
- [Core ChauffeEau Junkers Mid-1980s to Late 1990s](#)
- [Not recommended R410A to R407c](#)
- [Details of refrigerant R134a](#)
- [The electrical circuit for a timer-based steam refrigerator is an interesting one](#)
- [Changing Filter 1/5 Hp](#)
- [1/5 HP Compressor oil change: How much and how to do it right](#)
- [Deep cleaning AC units from A to Z... that's our craft](#)
- [Plumbing Fittings Explained](#)
- [Can the GL80 compressor be installed in place of the GL90?](#)
- [The process of replacing the air conditioner compressor is successful, and it is working as it was before ?](#)